

## SN-B series Main Technical Data:

TYPE	ITEM	SN-B600-2	SN-B600-3	SN-B600-4	SN-B600-6	SN-B1500-2	SN-B1500-3
CONTAINER	Number of cavity	2 cavities	3 cavities	4 cavities	6 cavities	2 cavities	3 cavities
	Output	2400-2700 pcs/hr	3000-3300 pcs/hr	5500-6000 pcs/hr	7000-8000 pcs/hr	2400-2600 pcs/hr	2800-3300 pcs/hr
	Max.container volume	0.6L	0.6L	0.6L	0.6L	1.5L	1.5L
	Max.neck diameter	65mm	65mm	65mm	28-30mm	80mm	80mm
	Max.container diameter	65mm	65mm	65mm	60mm	105mm	105mm
	Max.container height	230mm	230mm	230mm	260mm	300-330mm	300-330mm
ELECTRICAL SYSTEM	Number of lamp	21pcs	28pcs	35pcs	56pcs	27pcs	36pcs
	Max.heating power	21kw	28kw	29kw	57kw	35kw	36kw
	Installation power	24kw	28kw	37kw	65kw	42kw	48kw
	Actual power consumption	14kw	18kw	25kw	45kw	29kw	22kw
AIR SYSTEM	Operatating pressure	7-9kg/c m <sup>2</sup>	7-9kg/c m <sup>2</sup>	7-9kg/c m <sup>2</sup>	7-8kg/c m <sup>2</sup>	7-9kg/c m <sup>2</sup>	7-9kg/c m <sup>2</sup>
	Low pressure consuming	1000Ltr/min	1200Ltr/min	1600Ltr/min	1600Ltr/min	1200Ltr/min	1400Ltr/min
	Blowing pressure	25-35kg/c m <sup>2</sup>	25-35kg/c m <sup>2</sup>	25-35kg/c m <sup>2</sup>	25-35kg/c m <sup>2</sup>	25-35kg/c m <sup>2</sup>	25-35kg/c m <sup>2</sup>
	High pressure consuming	1500-2000 Ltr/min	2000-2200 Ltr/min	2200-2500 Ltr/min	2000-2200 Ltr/min	2000-2500 Ltr/min	2000-3000 Ltr/min
CHILLER WATER	Operating pressure	5-6 kg/c m <sup>2</sup>	5-6 kg/c m <sup>2</sup>	5-6 kg/c m <sup>2</sup>	5-6 kg/c m <sup>2</sup>	5-6 kg/c m <sup>2</sup>	5-6 kg/c m <sup>2</sup>
	Temperatuer	10℃	10℃	10℃	10℃	10℃	10℃
	Consuming	5600kcal/hr	5600kcal/hr	5600kcal/hr	8000kcal/hr	5600kcal/hr	7600kcal/hr
	Flow rater	30Ltr/min	30Ltr/min	30Ltr/min	88Ltr/min	30Ltr/min	45Ltr/min
MACHINE	Machine dimension	2.3x1.5x1.7(m)	2.7x1.5x1.7(m)	3.0x1.5x1.7(m)	5.2x2.0x2.0(m)	2.4x1.5x1.7(m)	2.7x1.5x1.7(m)
	Machine weight	1.8ton	2.5ton	2.8ton	5.0ton	2.0ton	2.6ton

TYPE	ITEM	SN-B1500-4	SN-B5000	SN-B5000-2	SN-B5000-4	SN-B10000
CONTAINER	Number of cavity	4 cavities	1 cavities	2cavities	4cavities	1 cavities
	Output	3800-4200 pcs/hr	650-800 pcs/hr	1200-1500 pcs/hr	2000-2200 pcs/hr	≥ 600pcs/hr
	Max.container volume	1.5L	5L	5L	5L	10L
	Max.neck diameter	80mm	45-80mm	45-80mm	45-80mm	45-80mm
	Max.container diameter	105mm	180mm	180mm	180mm	220mm
	Max.container height	300-330mm	350mm	350mm	350mm	400mm
ELECTRICAL SYSTEM	Number of lamp	54pcs	24pcs	36pcs	60pcs	36pcs
	Max.heating power	55kw	22kw	49kw	60kw	36kw
	Installation power	64kw	22kw	57kw	100kw	40kw
	Actual power consumption	44kw	18kw	40kw	36kw	28kw
AIR SYSTEM	Operatating pressure	7-9kg/c m <sup>2</sup>	7-9kg/c m <sup>2</sup>	7-9kg/c m <sup>2</sup>	7-9kg/c m <sup>2</sup>	7-9kg/c m <sup>2</sup>
	Low pressure consuming	2000 Ltr/min	1200 Ltr/min	1600 Ltr/min	2600 Ltr/min	1600 Ltr/min
	Blowing pressure	25-35kg/c m <sup>2</sup>	25-35kg/c m <sup>2</sup>	25-35kg/c m <sup>2</sup>	25-35kg/c m <sup>2</sup>	25-35kg/c m <sup>2</sup>
	High pressure consuming	3000-3500 Ltr/min	1200-1600 Ltr/min	2600-3000 Ltr/min	4500-5000 Ltr/min	1600-2000 Ltr/min
CHILLER WATER	Operating pressure	5-6 kg/c m <sup>2</sup>	5-6 kg/c m <sup>2</sup>	5-6 kg/c m <sup>2</sup>	5-6 kg/c m <sup>2</sup>	5-6 kg/c m <sup>2</sup>
	Temperatuer	10℃	10℃	10℃	10℃	10℃
	Consuming	7600kcal/hr	3600kcal/hr	4600kcal/hr	6600kcal/hr	5600kcal/hr
	Flow rater	45Ltr/min	20Ltr/min	30Ltr/min	45Ltr/min	30Ltr/min
MACHINE	Machine dimension	3.0x1.5x1.7 (m)	4.2x2.0x2.0(m)	4.8x2.0x2.0 (m)	5.6x2.0x2.0 (m)	4.3x2.0x2.0 (m)
	Machine weight	3.0ton	2.3ton	4.0ton	5.5ton	2.8ton